

SECTION 01501 - Control of Work

PART 1 - GENERAL

1.1 DESCRIPTION OF WORK

- A. The Contractor shall furnish personnel and equipment which shall be efficient, appropriate and large enough to secure a satisfactory quality of work and a rate of progress which will insure the completion of the work within the time stipulated in the Agreement. If any time such personnel appears to the Engineer to be inefficient, inappropriate or insufficient for securing the quality of work required for producing the rate of progress aforesaid, the Owner or Engineer may direct the Contractor to increase the efficiency, change the character or increase the personnel and equipment, and the contractor shall conform to such order. Failure of the Engineer or Owner to give such direction shall in no way relieve the Contractor of his/her obligations to secure the quality of the work and rate of progress required.

1.2 PRIVATE LAND

- A. The Contractor shall not enter or occupy private land outside of easements, except by permission of the Owner.

1.3 OPEN EXCAVATIONS

- A. All open excavations shall be adequately safeguarded by providing temporary barricades, caution signs, lights and other means to prevent accidents to persons, and damage to property. The contractor shall, at his / her own expense, provide suitable and safe bridges and other crossings for accommodating travel by pedestrians and workmen. Bridges provided for access to private property during construction shall be removed when no longer required. If the excavation becomes a hazard, or if it excessively restricts traffic at any point, the Engineer may require special construction procedures such as limiting the length of open trench, prohibiting stacking excavated material in the street or right-of-way, and requiring that the excavations shall not remain open when work is not in progress.
- B. The Contractor shall take precautions to prevent injury to the public due to open trenches and excavations. All trenches, excavated material, equipment, or other obstacles, which could be dangerous to the public, shall be well lighted and barricaded when work is not in progress.

PART 2 - PRODUCTS

NOT USED

PART 3 - EXECUTION

3.1 PROTECTION OF CONSTRUCTION AND EQUIPMENT

- A. All newly constructed work shall be carefully protected from injury in any way. No wheeling or walking or placing of heavy loads on it shall be allowed and all portions injured shall be reconstructed by the Contractor at his own expense.
- C. Further, the Contractor shall take all necessary precautions to prevent damage to any structure during and after construction and until such structure is accepted and taken over by the Owner.

*** * END OF SECTION * ***

CONTROL OF WORK